

Auto-Lock Kit

Panelift[®] Storm-Shield[™]

installation instructions PART NO: MS0104

installation

standard installation

garage door lock - order no. MC-0002					
item	description	qty			
1	garage door lock (includes battery)	1			
2	mounting plate MC0048	1			
3	bracket striker MC0010	1			
wireless WBS-1V1 kit 1 order 14827					
5	wireless WBS-1V1 AY	1			
6	WBS harness 90mm AY	1			
7	WBS harness 400mm AY	1			
8	taptite screw "P"	2			
9	velcro 20 x 50	1			
mounting screw pack GDL100 order 61411					
10	bolt 1/4" - 20TPI - UNCX1/2" SQ neck	3			
11	nut ser fing 1/4" x 20-TP1 UNC ZN	3			
12	screw tek 14g-20x25 flng HD CL4	4			
13	taptite screw MSHR head "P" M6 x 13	2			

important safety instructions

WARNING!

- DO NOT attempt to disassemble, repair or modify the product. This will invalidate the warranty.
- DO NOT allow children to play with the Auto-Lock.
- Not suitable for garages that have only one exit.
- DO NOT cover, paint or lubricate the product.

WARNING!

This device will slide a bolt into the guide track automatically when the door is closed. Not suitable for garages that have only one exit. For emergency lock/unlock press the button on the Auto-Lock. This will disengage the lock from the guide track and allow you to disengage the opener and open the door. The lock will automatically re-engage after the next complete cycle.

It is our strong recommendation that your opener be fitted with SAFETY BEAMS. Safety Beams detect any obstructions in the door/ gate's path and override automatic operation if one presents. These must be installed as in accordance with AS/NZS 60335-2-95:2012.

CAUTION!

Fall from ladder

- Ensure ladder is the correct type for job.
- Ensure ladder is on flat ground.
- Ensure user has 3 points of contact while on ladder.

Burns

- DO NOT handle damaged or leaking batteries
- The Auto-Lock Kit contains sealed lead-acid batteries that must be disposed of properly at the end of their useful life.



PART NO: MS0104. REVISION 1 - MAY 2017 These instructions are intended for professional garage door installers. All references are taken from inside looking out.

prior to installation

preparation - pull tab

- a. Prior to installation of the Auto-Lock, pull to remove the battery isolation tab.
- b. Once removed the battery will engage and the lock is operational.


Examine the garage and proceed to either Standard Installation on either L/h or R/h side of door.


standard installation


preparation - mounting on door stile


- a. Fit the mounting plate (2) to the garage door lock (1) using two button head screw ZN M6 x 14 screws (13).
- b. Close the door to determine mounting position between the reinforcing braces on the bottom door panel and mark. Fit the lock and lock plate assembly as marked with 2 only of the 4 tek screws 14g-20x25 fing HD CL4 to the inner two slots only as the outer two slots are covered by the tracklock and further final adjustment may be required.
- c. With the door in the closed position align the lock strike (3) with the lock allowing for vertical and horizontal movement of the door drill 2 x ¼ holes as marked in the tracklock and fix with 2 x 6mm 20-TPI UNC x 1/2 SQ neck bolts and nuts.
- d. Open and close the door, operate the lock manually make sure the lock bolt fully engages in the strike bracket without catching and adjust as required before fitting the remaining tek screws to the lock base plate and ensuring the three strike nuts and bolts are tight.


PROCEED TO CONNECTING WIRELESS BASE STATION TO THE OPENER.













connect transceiver to opener SDO-2V2 Advance[™], SDO-3 S & PanelPro[™]

preparation of opener

- a. Disconnect the power supply to the opener.
- b. Remove the back cover via screw at top.

to connect the harness and fit the transceiver

Advance[™]

- a. Remove the side flap from the left hand side of cover (1).
 Slide the WBS harness 90mm through the slot in the cover.
 Connect the harness to the 4 pin connector on the control board (2) as shown on the Advance control board. Plug the other end of the 90mm harness into the transceiver (3).
- b. Slide the aerial from the transceiver (4) through the slot in the cover as shown so that aerial hangs out of cover. Affix transceiver to opener with 1 x taptite screw (5).
- c. Refit all covers.

CAD S & PanelPro™

- a. Remove the grommet out of the chassis (6). Cut one side of the grommet with a knife. Slide the 400mm WBS harness into the cut in the grommet. Refit grommet to chassis by sliding the harness through hole before fitting grommet. Connect the harness to the 4 pin connector (7) on the control board as shown.
- b. Attach the other end of the 400mm WBS harness to the transceiver, **(8)** using the velcro tape attach the transceiver onto the top of the opener as shown.
- c. Refit all covers.

WARNING! DO NOT drill into the chassis or covers. No screws are required to secure the wireless basestation (except for the Advance[™] which has a predrilled hole).

test the opener

- a. Reconnect power to the opener and test operation.
- b. Upon completion of a full cycle the lock will engage into the track.


operation

how to operate


Press the emergency lock/ unlock button on the front of the Auto-Lock to disengage the lock from the guide track and allow you to disengage the opener and open the door.

WARNING! The emergency lock/unlock button on this product is not to be used as a primary means of locking the door under normal circumstances.

The emergency lock/unlock button is to be used only in case of power outage or emergency.




(8) attach with velcro tape



battery change

low battery warning

- a. Replace lock batteries (2 x C-LR 14) immediately when opener light flashes three times.
- b. Remove cover by unscrewing the two screws on the main cover.
- c. Replace batteries and refit cover and secure with two screws.





warranty and exclusion of liability

purchased from:		purchaser:	(described as "you" k	oelow)
address:		installed by:	:	
installed on (date):	invoice no:		
 Installed on (date) Making a claim To make a warranty produce a copy off certificate with the of below; or where the Product h with B&D by sending below; or where the Product h warranty claims dire correct address of th product, you can se completed, includin the distributor. 8&D or approved dis This warranty is in ad warranty upplies on "B&D" means in Aus 2212 and in New Zec Tamaki Auckland. "X B&D products purch supplying those prod What the warranty c B&D by any and the second product has been in b. in materials, manufc i. for all componen the powerheads i for all componen the delivery or installad reinstallation and walid for a period iv. in each case the delivery or installad this warranty does n batteries or globes - b. adjustments - (cas de Product) which are r adjustments; model modifications made to existing/fut travel expenses - inc travelling to and fror capital city metropoce additional access et obtaining access withing access withing	claim you must: he receipt of purchase, together with this warr above details completed; and ias been sold by B&D, make all warranty claim g it to B&D at the relevant address set out in pa- cas been sold by an approved distributor, make citly with the approved distributor. If you are un- e approved distributor from which you purche ind your claim to B&D with the rest of the abov g the original invoice number, and we will forv for the expense of making a claim under this w stributors only diltion to any statutory, non-excludable guara er Australian or New Zealand laws (as applicab ly to Products sold by B&D or its approved distributor for the expense of Making a Claim under the wear asing on open account, from B&D, for the pur- ducts to end users. Overs ct to paragraph 4, that it will, at its option, eith eriod of one year from the date of installation stalled by B&D or its approved distributor; acture or workmanship in the Product, as follow ts of the Product that make up the power hear installation manual; ts of the Product that make up the power hear ick assembly) that is attached to a garage do led by B&D or an approved distributor, the war of one year; and warranty applies from the later of the date of attion by B&D or an approved distributor, the war of one year; and warranty applies from the later of the date of attion by B&D or an approved distributor (as ap oes not cover ot cover: B&D will not be liable for any defect or failure scribed in the Instruction Manual provided wit not defects - you will need to pay for any servic scribed in the Instruction Manual provided wit not defects - you will need to pay for these expo- yure Product models; urred by B&D or its approved distributor in eith n or transporting the Product to/from areas ou- pliftan area - you will need to pay for these expo- yure approved distributor in eith n or transporting the Product to/from areas ou- pliftan area - you will need to pay for these expo- yue product models; nor reading accessible - you	invoice no: anty s directly ragraph 2 e all ssure of the ssed the e details vard it to varranty. Intees or by NSW bad, East biler of pose of er repair or cts: where the rs: d refer to d or and rranty is purchase, plicable). in them; h the ce calls for tiside a enses; or ributor in	 c. other devices - the Product being fitted to any door or other closing du which is not of the type or condition defined in the Instruction Manual suitable for installation of the Product; d. installation or adjustment - faulty installation or adjustment of the Product is connected where such installation or adjustment is not carried out by 8&D or its approved distributors; e. unauthorised cats: modifications or repairs made or attempted to be by you or any unauthorised person; f. service - lack of proper maintenance, service or care of the door and Product; g. outside control - events or acts beyond the reasonable control of 8&D h. settings - use with doors locked or operation of the Product with excess high opening or closing force settings l. wiring - faulty electrical wiring of structures to which the Product is affit; j. interference - radio (including citizen brand transmissions) or other ele interference; k. water damage - including effects from rust and corrosion); l. salt - salt corrosion or damage to the surface coatings or base materia due to environmental conditions (such as proximity to the sea-front or corrosive conditions). m. continuous operating firme - maximum continuous operating time excel 1 minute in 10; n. maximum operating force - the operating force exceeding 15kg* (150 Newton) when moving the door manually to the open or closed positi c. door size - the door surface area exceeding 16.5m2; p. modifications - any unauthorised modification Consumer Law, our goads with guarantees or warranties Australia Kaustraia If you are a consumer under the Australian Consumer Law, our goads with guarantees or warranties and the failure does not amound to a major failure on compensation for any other reasonably foreseeable loss or damage. The you are also entilled to a hey beck sepaired or replaced if the goads be of acceptable quality and the failure does not amound to a major	I as duct a made d D; ssively ixed; ectronic als r similar ceeding D o ion; in a family fail to failure. ment fy the Law. ment fy the ely utory d that mit its ity for duct or 5 010
relieved of, all obliga		nt that	63 and email enquiries@bnd.com.au. In New Zealand, this warranty is given by BD Doors (NZ) Limited of 30C Road, East Tamaki, Auckland, phone 09-273 8600 and email enquiries co.nz. This warranty document is not intended to create a contract be B&D and the purchaser.	@bnd.
the Instruction Manu b. instructions - failure t	the Product not being used correctly in accord ad or other unreasonable use; to observe any instructions or directions (includ ons in the Instruction Manual), provided with th	ding	 Notes The door that the Product is used with should be balanced in such a that the user is able to open or close the door manually using a force is greater than 150 Newton (15 kg), other than to initially cause the door start moving, which may require force in excess of that specified in this paragraph. 	not ´ r to
b&d doors of	fice locations		your representative is	
New South Wales	34 Marigold St, Revesby 2212	Phone (02)	9722 5555	
Queensland	17 Oasis Court, Clontarf 4019	Phone (07)	0 3883 0200	

Phone (02) 4956 8533

Phone (03) 9237 7766

Phone (08) 8440 4747

Phone (08) 9247 8777

Phone +61 (0)2 9722 5555

Prefixed trademarks are the property of B&D Australia Pty Ltd. B&D Doors & Openers is a division of B&D Australia Pty Ltd. ABN 25 010 473 971. © 2016 B&D Australia Pty Ltd.

Unit 1/108 Mitchell Rd, Cardiff 2285

147-153 Canterbury Rd, Kilsyth 3137

23 Frederick Rd, Royal Park 5014

96 Mulgul Rd, Malaga 6090

34 Marigold St, Revesby 2212

www.bnd.com.au

Newcastle

South Australia

Western Australia

International/Export

Victoria

 $\mathbf{O80}$